

S1

PRO series



Product Name: S1

Product Number: 700S1

Description

Flashlight with 49 + 420 lumens and sliding focus

Specifications

Housing	Aluminium
Lens	Acrylic, optical
On/off switch	Bottom, red ABS
Battery type	4 x AAA Alkaline Duracell
Light source	5W CREE XPG2-R4
Colour temperature (Kelvin)	7500K
Focus	Sliding style optical focus system
Charger operating voltage	N/A
Charger output	N/A
Output 30 seconds (lumen)	49 (low beam) / 420 (high beam)
Max output 3 seconds (lumen)	N/A
Run time (hours) down to 1 lumen	51 (low beam) / 13 (high beam)
Run time (hours) down to 10% of full lumens	10.4 (low beam) / 2.2 (high beam)
Beam distance (m)	27 (low beam) / 250 (high beam)
Beam width (cm) from 1m distance	160 (flood) / 15 (spot)
Protection class	IP65 / IK07 / III
Operating temperature range (Celsius)	-5°C to +40°C
Additional data	Stepless dimming through switch modes



General Information

Torch weight (g)	176 incl batteries (44g)
Torch dimensions (cm)	3.7/2.95 (diam. head/tube) x 12.2/13.7 (length flood/spot)
EAN code box (1 pc)	5703296700306
EAN code inner carton/display	5703296710305
EAN code outer carton	5703296720304
Harmonized standard code	8513100000

Packaging

Description	"PRO" design printed box
Box size (cm)	16.5 x 8 x 7.5
Box weight (g)	360
Carton quantity (pcs)	8 (inner carton) / 32 (outer carton)
Carton size (cm)	34 x 17 x 16.5 (inner carton) / 36 x 35 x 35 (outer carton)
Carton weight (kg)	3.05 (inner carton) / 13 (outer carton)



Features

Lightweight torch with sliding focus
Switch mode: high-low-strobe-emergency flash-SOS-off
Supplied with pouch and lanyard



Elwis Lighting A/S, Sandtoften 11, 2820 Gentofte, DK
www.elwislighting.com - Tel. +45 70 20 10 24

Version 3 10/2017
© Elwis Lighting 2017
All details without obligation